



8262 DECT HANDSET: RUGGEDIZED & LONE WORKER PROTECTION



DECT SETS RANGE



8232 DECT

8242 DECT



8262 DECT



- AGAP on IP DECT and TDM DECT for OXE
- OT design, Color Screen
- Hand-free, Vibrator, Automatic band Switching Ready

- Large screen 2,4”
- Emergency key, Compatible with Server Side DECT API
- Location and notification embedded applications
- Bluetooth Headset

- Ruggedized IP65
- Isolated Worker Protection
- Vertical Market Oriented
- Bluetooth Low Energy

PTI & Industrial 8262 DECT Handset

Overview

8262 :



Handset



Key facts

Display

Color 2,4" screen with backlight QVGA (320x240)

Connectivity

DECT AGAP/ CAT-iq
Bluetooth Low Energy for audio headsets & Location
Radio Frequency Identification (module optional)

Ingress Protection

High Level Protection Against Dust and Water (IP 65)

Call server connectivity

OXE: AGAP R100
OXO: AGAP on TDM IBS, CAT-iq on IP-DECT

Embedded Alarm Application in AGAP & CAT-IQ

Push button alarm, Location & Alarming
Pull cord alarm
Accelerator sensor : Man down, shock, No movement detection

8262 DECT handset accessories



Chargers
(single or rack dual charger)



Clips



Pouch



Accessories kit



Pull Cord



Spare battery



USB PSU

API DECT for advanced services with 3rd Party notification server

500 EX, 8262, 8242 DECT set user interface

Emergency: Sending an alert by long press
8242 & 8262 DECT triggers: Red and/or OK keys
500 EX DECT triggers: Red and/or OK keys

Alarms (8262 & 500 EX DECT sets)

- Man down
- No Movement
- Pull Cord



Man down
> 30-40-60°

Notification: Alert message reception with specific ringing



8242, 8262 and 500 EX DECT triggers: normal alarm, urgent alarm, very urgent alarm and another alarm with hand-free forcing

Process: Key info sent to the server by long pressing key in communication or not
8242 & 8262 DECT triggers: 0,1,2,3,4,5,6,7,8,9 keys
500 EX DECT triggers: 1,2,3,4,5,6,7,8,9 keys

Alarm triggers

Monitoring (8242, 8262, 500 EX, DECT): In-Out of charger and Handset on/off

8262 DECT handset: Alarms capabilities

Alarm configuration menu

(Protected by a password, so the end-user is not able to change the alarm settings):

- Alarms trigger
 - Emergency call
 - Mandown
 - No Movement
 - Shock
 - Pull Cord
- Location & events
 - Live (enable/disable)
 - Status (enable/disable)
 - Key events (enable/disable)
 - Bluetooth Low energy location




Alarm ack menu:

- To send alarm acknowledge (if location audio signal is playing, ringing is stopped after acknowledge)
- to create a pin code. The acknowledge can be protected by a specific PIN code, when security process requires that only security officer can stop location audio signal

PRODUCT OVERVIEW INFRASTRUCTURE SUPPORT

Full Integration with OTNS Eco-System

- ✓ Notifications
- ✓ Emergency Key
- ✓ Geo Localization
 - ✓ DECT
 - ✓ Bluetooth Low Energy
- ✓ PTI
 - ✓ Man down
 - ✓ No Movement
 - ✓ Pull cord



enterprise.alcatel-lucent.com